Degree of protection: IP65

Housings, cable to cable, high	1					
construction	Thread	Designation		Order No.		
	M25	W16B-CCTH-2	L/ <mark>SC</mark> -M25	111 116 741 5002		
teo.	M32	W16B-CCTH-2	L/ <mark>SC</mark> -M32	111 116 741 5003		
	M40	W16B-CCTH-2	_/ <mark>SC</mark> -M40	111 116 741 5004	95	
	PG21	W16B-CCTH-2	L/ <mark>SC</mark> -PG21	111 116 741 5005		
	PG29	W16B-CCTH-2	L/ <mark>SC</mark> -PG29	111 116 741 5006		י) דעי ⊔
		with sleeve				-78.5
	M32	W16B-CCTH-2	L/ <mark>SC</mark> -M32 <mark>WS</mark>	111 116 741 5013		
	PG21	W16B-CCTH-2	L/ <mark>SC</mark> -PG21 WS	111 116 741 5011	- M/PG-	
	PG29	W16B-CCTH-2	L/ <mark>SC</mark> -PG29 WS	111 116 741 5012		
	Please refer to pa	ige 15-02 for choosing prop	er model of lock.			
Protection covers, plastic						
	Thread Applic	ations Designation		Order No.		
	for ho	ods H16B-CV-4C		111 016 090 8009		
(m)=15					96.5	
Protection covers, plastic						
	Connect way	Applications	Designation	Order No.		
	~0	for Housings, cable to cable	H16B-CV-4B/1	111 016 030 8001		
	_~~~	for Housings, bulkhead	H16B-CV-4B/2	111 016 030 8002		
-		mounting /surface mounting				
Laure .					97.3	<u>S</u> <u>45</u> 57