## Degree of protection: IP65

lousings, cable to cable, high						
construction	Thread	Designation		Order No.		
	M32	W24B-CCTH-2L/SC-	M32	111 124 741 5002		
	M40	W24B-CCTH-2L/SC-	M40	111 124 741 5003	+22+	t 45
R	PG21	W24B-CCTH-2L/SC-	PG21	111 124 741 5004		
	PG29	W24B-CCTH-2L/SC-	PG29	111 124 741 5005		
		with sleeve				v¶∕   \¶ <sup>µ</sup>
	M32	W24B-CCTH-2L/SC-	M32 <mark>WS</mark>	111 124 741 5010		
	PG21	W24B-CCTH-2L/SC-	PG21 WS	111 124 741 5011		
	PG29	W24B-CCTH-2L/SC-	PG29 WS	111 124 741 5012	↓M/PG↓	
	Please refer to p	age 15-02 for choosing pro	per model of lock.			
rotection covers, plastic			·			
otection covers, plastic	Connect way	Applications De	signation	Order No.		
			4B-CV-4C	111 024 090 8009		
		101110003 112		111 024 050 0005		
						FAF
						45.5
						56
otection covers, plastic	<b>C</b>	A	B i	OudenNie		
	Connect way	Applications	Designation	Order No.		
-	_~O	for Housings, cable to cable	,	111 024 030 8001		
	O	for Housings, bulkhead	H24B-CV-4B/2	111 024 030 8002		
		mounting /surface mounting				r A
La					124.1	45
Lat.					- 1670 -	- 2/