

HD-064 Ultra-high density inserts

250V 10A 64+ 

Inserts

Hoods/Housings: size 24B, please find the details on page 15-108~15-150.

Crimp terminal


order crimp contacts separately




The insert only matches 10A stamped contacts.

Insert	Designation	Order No.
Male	HD-064-MC/P	125 064 010 0021
	HD-064-FC/P	125 064 020 0021


1) Distance for contact max. 21 mm



Contact arrangement view from termination side



Panel cut out for inserts for use without hoods/housings



Crimp contacts

Stamped contacts10A


silver plated



coil stock



Wire gauge	contacts	Designation	Order No.
0.5-1.5mm ²	male	CDSM-1.5P	101 017 110 0905
	female	CDSF-1.5P	101 017 120 0905
1.5-2.5mm ²	male	CDSM-2.5P	101 017 110 1005
	female	CDSF-2.5P	101 017 120 1005



Tools

Crimping tool



Contact removal tool



Wire gauge	Designation	Order No.
0.5-2.5mm ²	TL14	198 001 001 0022

Application	Designation	Order No.
10A male contacts	TL00	198 001 000 0001
10A female contacts	TL13	198 001 000 0025

*Please find the details of crimp contact tools on page 32-03~32-06.

Notes: The tools for crimp terminal may influence the product quality and stability. Please select the tools recognized by our company.