

HMDD-017 Crimp module

160V 10A

Inserts



Combination with hinged frame and other modules possible.


Technical characteristics

Specifications	DIN EN 60 664 DIN EN 61 984		
Approvals			
Inserts		Contacts	
Number of contacts	17	Material	copper alloy
Electrical data acc. to EN 61 984		Surface	hard-silver plated hard-gold plated
-Rated current	10A	Contact resistance	≤ 3mΩ
-Rated voltage	160V	Crimp terminal	
-Rated impulse voltage	2.5kV	-mm ²	0.14-2.5mm ²
-Pollution degree	3	-AWG	26-14
Rated voltage acc. to UL	250V		
Insulation resistance	≥ 10 ¹⁰ Ω		
Material	polycarbonate		
Limiting temperatures	-40°C ... +125°C		
Flammability acc. to UL 94	V0		
Mechanical working life			
- mating cycle	≥ 500		

Current carrying capacity

The current carrying is limited by maximum temperature of materials for inserts and contacts including terminals

Control and test procedures according to DIN EN 60512-5




— 24 B hoods/housings with 6 modules, wire gauge: 1.5mm²
— 24 B hoods/housings with 6 modules, wire gauge: 1.0mm²

Crimp terminal

Order crimp contacts separately



Insert	Designation	Order No.
Male	HMDD-017-MC	129 017 010 0001
Female	HMDD-017-FC	129 017 020 0001



Crimp contacts

Crimp contacts 10A

Contact resistance ≤ 3mΩ
silver plated

gold plated

More crimp contacts 10A
see P13-02, P13-02.

Tools

Crimping tool




Contact removal tool



Male	Order No.	Female	Order No.
CDSM-0.25	101 017 110 0101	CDSF-0.25	101 017 120 0101
CDSM-0.37	101 017 110 0301	CDSF-0.37	101 017 120 0301
CDSM-0.50	101 017 110 0401	CDSF-0.50	101 017 120 0401
CDSM-0.75	101 017 110 0601	CDSF-0.75	101 017 120 0601
CDSM-1.0	101 017 110 0801	CDSF-1.0	101 017 120 0801
CDSM-1.5	101 017 110 0901	CDSF-1.5	101 017 120 0901
CDSM-2.5	101 017 110 1001	CDSF-2.5	101 017 120 1001
CDGM-0.25	101 017 210 0101	CDGF-0.25	101 017 220 0101
CDGM-0.37	101 017 210 0301	CDGF-0.37	101 017 220 0301
CDGM-0.50	101 017 210 0401	CDGF-0.50	101 017 220 0401
CDGM-0.75	101 017 210 0601	CDGF-0.75	101 017 220 0601
CDGM-1.0	101 017 210 0801	CDGF-1.0	101 017 220 0801
CDGM-1.5	101 017 210 0901	CDGF-1.5	101 017 220 0901
CDGM-2.5	101 017 210 1001	CDGF-2.5	101 017 220 1001

Wire gauge	Designation	Order No.
0.14-4mm ²	TL02G	198 001 001 0011
For the crimping contacts and removing contacts instructions, please find the page 06-23-06-24.		
Application	Designation	Order No.
for crimp contacts 10A	TL00	198 001 000 0001
More tools detail please find the page 32-03-32-06.		



Wire gauge	Φ	Stripping length
0.09-0.25 mm ² AWG 28-24	0.65	5 mm
0.14-0.37 mm ² AWG 26-22	0.9	8 mm
0.5 mm ² AWG 20	1.1	8 mm
0.75 mm ² AWG 18	1.3	8 mm
1 mm ² AWG 18	1.45	8 mm
1.5 mm ² AWG 16	1.75	8 mm
2.5 mm ² AWG 14	2.25	6 mm

When the wire gauge is less than 0.75mm², it's better to use the auxiliary pin assembly tool TL15.

Notes: The tools for crimp terminal may influence the product quality and stability. Please select the tools recognized by our company.