

M8 Circular Connector

30/60V 4A

Technical characteristics

	3-pole	4-pole
Rated current(40°C)	4A	4A
Rated voltage	60V	30V
Rated impulse voltage	800V	800V
Pollution degree	3	3
Overvoltage categorie	II	II
Contact resistance	≤ 10 mΩ	≤ 10 mΩ
Connector locking system	screw	screw
Termination	screw	screw,
Wire gauge	screw 0.14-0.5mm²(AWG26-20)	screw 0.14-0.5mm²(AWG26-20)
Cable outlet	3.5-5.5 mm	3.5-5.5 mm
Degree of protection	IP67	IP67
Mechanical operation	> 100	> 100
Limiting temperature	-40°C ...+85°C	-40°C ...+85°C
Material group	III	III
Material of contact	copper alloy	copper alloy
Contact plating	Au	Au
Insulating material	PA	PA
Material of housing	CuZn	CuZn

Straight cable connectors, shielded

Female cable connector, solder, shielded

Recommend to use

Contacts	Cable outlet	Designation	Order No.
3	3.5-5 mm	M8-F03-S-D5.5-SH	162 003 502 2007
4	3.5-5 mm	M8-F04-S-D5.5-SH	162 004 502 2003



Contact arrangements

