

## M12-A Circular Connector

60/125/250V 2/4A

## Technical characteristics


|                          | 3-pole                              | 4-pole                              | 5-pole                              | 8-pole                              |
|--------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Rated current (40°C )    | 4A                                  | 4A                                  | 4A                                  | 2A                                  |
| Rated voltage            | 250V                                | 250V                                | 125V                                | 60V                                 |
| Rated impulse voltage    | 2500V                               | 2500V                               | 1500V                               | 800V                                |
| Pollution degree         | 3                                   | 3                                   | 3                                   | 3                                   |
| Overvoltage categorie    | II                                  | II                                  | II                                  | II                                  |
| Contact resistance       | ≤ 10 mΩ                             | ≤ 10 mΩ                             | ≤ 10 mΩ                             | ≤ 10 mΩ                             |
| Connector locking system | screw M12x1                         | screw M12x1                         | screw M12x1                         | screw M12x1                         |
| Termination              | screw/solder                        | screw/solder                        | screw/solder                        | solder                              |
| Wire gauge               | max.0.75mm <sup>2</sup> (max.AWG18) | max.0.75mm <sup>2</sup> (max.AWG18) | max.0.75mm <sup>2</sup> (max.AWG18) | max.0.75mm <sup>2</sup> (max.AWG18) |
| Cable outlet             | 4-6,6-8 mm                          | 4-6,6-8 mm                          | 4-6,6-8 mm                          | 4-6,6-8 mm                          |
| Degree of protection     | IP67                                | IP67                                | IP67                                | IP67                                |
| Mechanical operation     | > 100                               | > 100                               | > 100                               | > 100                               |
| Limiting temperature     | -40°C ...+85°C                      | -40°C ...+85°C                      | -40°C ...+85°C                      | -40°C ...+85°C                      |
| Material group           | II                                  | II                                  | II                                  | II                                  |
| Material of contact      | copper alloy                        | copper alloy                        | copper alloy                        | copper alloy                        |
| Contact plating          | Au                                  | Au                                  | Au                                  | Au                                  |
| Insulating material      | PA                                  | PA                                  | PA                                  | PA                                  |
| Material of housing      | PA/PBT                              | PA/PBT                              | PA/PBT                              | PA/PBT                              |

## Angled cable connectors

Male cable connector, plastic locking system, screw clamp connection



| Contacts | Cable outlet | Designation    | Order No.        |
|----------|--------------|----------------|------------------|
| 3        | 4-6 mm       | M12P-M03A-S-D6 | 163 003 511 3101 |
|          | 6-8 mm       | M12P-M03A-S-D8 | 163 003 511 3102 |
| 4        | 4-6 mm       | M12P-M04A-S-D6 | 163 004 511 3101 |
|          | 6-8 mm       | M12P-M04A-S-D8 | 163 004 511 3102 |
| 5        | 4-6 mm       | M12P-M05A-S-D6 | 163 005 511 3101 |
|          | 6-8 mm       | M12P-M05A-S-D8 | 163 005 511 3102 |




A-Code



Male cable connector, plastic locking system, solder



| Contacts | Cable outlet | Designation      | Order No.        |
|----------|--------------|------------------|------------------|
| 3        | 4-6 mm       | M12P-MST03A-S-D6 | 163 003 513 3500 |
|          | 6-8 mm       | M12P-MST03A-S-D8 | 163 003 513 3501 |
| 4        | 4-6 mm       | M12P-MST04A-S-D6 | 163 004 513 3500 |
|          | 6-8 mm       | M12P-MST04A-S-D8 | 163 004 513 3501 |
| 5        | 4-6 mm       | M12P-MST05A-S-D6 | 163 005 513 3500 |
|          | 6-8 mm       | M12P-MST05A-S-D8 | 163 005 513 3501 |
| 8        | 4-6 mm       | M12P-MST08A-S-D6 | 163 008 513 3500 |
|          | 6-8 mm       | M12P-MST08A-S-D8 | 163 008 513 3501 |



A-Code

