

M12-B Circular Connector

125/250V 4A

Technical characteristics

	4-pole	5-pole
Rated current(40°C)	4A	4A
Rated voltage	250V	125V
Rated impulse voltage	2500V	1500V
Pollution degree	3	3
Overvoltage categorie	II	II
Contact resistance	≤ 10 mΩ	≤ 10 mΩ
Connector locking system	Thread	Thread
Termination	solder,single-strand wires	solder,single-strand wires
Wire gauge	max.0.75mm ² (AWG18)	max.0.75mm ² (AWG18)
Cable outlet	-	-
Degree of protection	IP67	IP67
Mechanical operation	> 100	> 100
Limiting temperature	-40°C ...+85°C	-40°C ...+85°C
Material group	II	II
Material of contact	copper alloy	copper alloy
Contact plating	Au	Au
Insulating material	PA	PA
Material of housing	zinc diecasting nickel plated	zinc diecasting nickel plated

Socket

Female panel mount connector
with single wires, /0.25mm²/length
0.2m



B-Code



Female panel mount connector, solder
PG9/M16x1.5



B-Code



Female panel mount connector,
dip solder



B-Code



Contacts	Thread	Designation	Order No.
4	PG9	M12-F04B-BK-PG9-W0.25	163 004 302 4003
	M16x1.5	M12-F04B-BK-M16-W0.25	163 004 302 4004
5	PG9	M12-F05B-BK-PG9-W0.25	163 005 302 4007
	M16x1.5	M12-F05B-BK-M16-W0.25	163 005 302 4008

Customized cable length upon request

Contacts	Thread	Designation	Order No.
4	PG9	M12-F04B-BK-PG9-C	163 004 323 1002
	M16x1.5	M12-F04B-BK-M16-C	163 004 323 1003
5	PG9	M12-F05B-BK-PG9-C	163 005 323 1002
	M16x1.5	M12-F05B-BK-M16-C	163 005 323 1003

Contacts	Thread	Designation	Order No.
4	PG9	M12-F04B-BK-PG9-D	163 004 324 1003
	M16x1.5	M12-F04B-BK-M16-D	163 004 324 1004
5	PG9	M12-F05B-BK-PG9-D	163 005 324 1003
	M16x1.5	M12-F05B-BK-M16-D	163 005 324 1004

