

M12-A Circular Connector

60/125/250V 2/4A

Technical characteristics

	4-pole	5-pole	8-pole
Rated current (40°C)	4A	4A	2A
Rated voltage	250V	125V	60V
Rated impulse voltage	2500V	1500V	800V
Pollution degree	3	3	3
Overvoltage categorie	II	II	II
Contact resistance	≤ 10 mΩ	≤ 10 mΩ	≤ 10 mΩ
Connector locking system	screw M12x1	screw M12x1	screw M12x1
Termination	single-strand wires	single-strand wires	single-strand wires
Wire gauge	max.0.75mm ² (max.AWG18)	max.0.75mm ² (max.AWG18)	max.0.34mm ² (max.AWG22)
Cable outlet	-	-	-
Degree of protection	IP67	IP67	IP67
Mechanical operation	> 100	> 100	> 100
Limiting temperature	-40°C ...+85°C	-40°C ...+85°C	-40°C ...+85°C
Material group	II	II	II
Material of contact	copper alloy	copper alloy	copper alloy
Contact plating	Au	Au	Au
Insulating material	PA	PA	PA
Material of housing	zinc diecasting nickel plated	zinc diecasting nickel plated	zinc diecasting nickel plated

Socket

Male panel mount connector,
solder

Recommended use



Contacts	screw	Designation	Order No.
4	PG9	M12-M04A-BK-PG9-C	163 004 313 1001
	M16x1.5	M12-M04A-BK-M16-C	163 004 313 1021
5	PG9	M12-M05A-BK-PG9-C	163 005 313 1001
	M16x1.5	M12-M05A-BK-M16-C	163 005 313 1021
8	PG9	M12-M08A-BK-PG9-C	163 008 313 1001
	M16x1.5	M12-M08A-BK-M16-C	163 008 313 1021
12	PG9	M12-M12A-BK-PG9-C	163 012 313 1500
	M16x1.5	M12-M12A-BK-M16-C	163 012 313 1501

A-Code



4pin




5pin



8pin

Customized cable length upon request



M12-A