

M12-A Circular Connector

30/60/125/250V 1.5/2/4A

Technical characteristics

	3-pole	4-pole	5-pole	8-pole	12-pole
Rated current (40°C)	4A	4A	4A	2A	1.5A
Rated voltage	250V	250V	125V	60V	30V
Rated impulse voltage	2500V	2500V	1500V	800V	800V
Pollution degree	3	3	3	3	3
Overvoltage categorie	II	II	II	II	II
Contact resistance	≤ 10 mΩ	≤ 10 mΩ	≤ 10 mΩ	≤ 10 mΩ	≤ 10 mΩ
Connector locking system	screw M12x1	screw M12x1	screw M12x1	screw M12x1	screw M12x1
Termination	screw/solder	screw/solder	screw/solder	screw/solder	solder
Wire gauge	max.0.75mm ² (max.AWG18)	max.0.75mm ² (max.AWG18)	max.0.75mm ² (max.AWG18)	max.0.5mm ² max.AWG20)	max.0.25mm ² max.AWG24)
Cable outlet	4-6,6-8 mm	4-6,6-8 mm	4-6,6-8 mm	6-8 mm	6-8 mm
Degree of protection	IP67	IP67	IP67	IP67	IP67
Mechanical operation	> 100	> 100	> 100	> 100	> 100
Limiting temperature	-40°C ...+85°C	-40°C ...+85°C	-40°C ...+85°C	-40°C ...+85°C	-40°C ...+85°C
Material group	III	III	III	III	III
Material of contact	copper alloy	copper alloy	copper alloy	copper alloy	copper alloy
Contact plating	Au	Au	Au	Au	Au
Insulating material	PA	PA	PA	PA	PA
Material of housing	PA/PBT	PA/PBT	PA/PBT	PA/PBT	PA/PBT


Straight cable connectors

Male cable connector, stainless steel


locking system, screw clamp connection,



A-Code



Contacts	Cable outlet	Designation	Order No.
3	4-6 mm	M12S-M03A-T-D6	163 003 401 3001
	6-8 mm	M12S-M03A-T-D8	163 003 401 3002
4	4-6 mm	M12S-M04A-T-D6	163 004 411 3201
	6-8 mm	M12S-M04A-T-D8	163 004 411 3202
5	4-6 mm	M12S-M05A-T-D6	163 005 411 3201
	6-8 mm	M12S-M05A-T-D8	163 005 411 3202
8	6-8 mm	M12S-M08A-T-D8	163 008 411 3202




M12-A

Male cable connector, stainless steel


locking system, solder



A-Code



Contacts	Cable outlet	Designation	Order No.
3	4-6 mm	M12S-MST03A-T-D6	163 003 413 3502
	6-8 mm	M12S-MST03A-T-D8	163 003 413 3503
4	4-6 mm	M12S-MST04A-T-D6	163 004 413 3504
	6-8 mm	M12S-MST04A-T-D8	163 004 413 505
5	4-6 mm	M12S-MST05A-T-D6	163 005 413 3502
	6-8 mm	M12S-MST05A-T-D8	163 005 413 3503
8	4-6 mm	M12S-MST08A-T-D6	163 008 413 3504
	6-8 mm	M12S-MST08A-T-D8	163 008 413 3505
12	6-8 mm	M12S-MST12A-T-D8	163 012 413 3004



Hexagonal driver



Description	Designation	Order No.
for 8 pin screw clamp connection	SW-1.27*47	198 001 003 0016