

M12-A Circular Connector

60/125/250V 2/4A

Technical characteristics

	4-pole	5-pole	8-pole	12-pole
Rated current (40°C)	4A	4A	2A	1.5A
Rated voltage	250V	125V	60V	60V
Rated impulse voltage	2500V	1500V	800V	800V
Pollution degree	3	3	3	3
Overvoltage categorie	II	II	II	II
Contact resistance	≤ 10 mΩ	≤ 10 mΩ	≤ 10 mΩ	≤ 10 mΩ
Connector locking system	screw M12x1	screw M12x1	screw M12x1	screw M12x1
Termination	single-strand wires	single-strand wires	single-strand wires	single-strand wires
Wire gauge	max.0.75mm ² (max.AWG18)	max.0.75mm ² (max.AWG18)	max.0.34mm ² (max.AWG22)	max.0.14mm ² (max.AWG26)
Cable outlet	-	-	-	-
Degree of protection	IP67	IP67	IP67	IP67
Mechanical operation	> 100	> 100	> 100	> 100
Limiting temperature	-40°C ...+85°C	-40°C ...+85°C	-40°C ...+85°C	-40°C ...+85°C
Material group	II	II	II	II
Material of contact	copper alloy	copper alloy	copper alloy	copper alloy
Contact plating	Au	Au	Au	Au
Insulating material	PA	PA	PA	PA
Material of housing	zinc diecasting nickel plated	zinc diecasting nickel plated	zinc diecasting nickel plated	zinc diecasting nickel plated

Socket

Male panel mount connector

with single wires, 0.25mm²

length 0.2m

Recommended use




A-Code



Contacts	screw	Designation	Order No.
4	PG9	M12-M04A-BK-PG9-W0.25	163 004 301 4001
	M16x1.5	M12-M04A-BK-M16-W0.25	163 004 301 4021
5	PG9	M12-M05A-BK-PG9-W0.25	163 005 301 4001
	M16x1.5	M12-M05A-BK-M16-W0.25	163 005 301 4021
8	PG9	M12-M08A-BK-PG9-W0.25	163 008 301 4001
	M16x1.5	M12-M08A-BK-M16-W0.25	163 008 301 4021
12	PG9	M12-M12A-BK-PG9-W0.14	163 012 301 4001
	M16x1.5	M12-M12A-BK-M16-W0.14	163 012 301 4002

Customized cable length upon request



Male panel mount connector


with single wires, 0.25mm²

length 0.2m

Recommended use



A-Code



Contacts	screw	Designation	Order No.
4	M16x1.0	M12-M04A-BK-M16*1.0-W0.25	163 004 301 4505
5	M16x1.0	M12-M05A-BK-M16*1.0-W0.25	163 005 301 4506
8	M16x1.0	M12-M08A-BK-M16*1.0-W0.25	163 008 301 4507

Customized cable length upon request

