

M17 Circular connector

63V- 3.6A

Technical characteristics

Specifications			
Specifications	DIN EN 60 664		
	DIN EN 61 984		
Approvals			
Electrical data		Mechanical data	
Number of contacts	17	Housing material	copper alloy,zinc alloy
Rated current	3.6A	Housing surface	Nickel-plated
mm ² / AWG	(0.14-0.5 mm ² / AWG 26-20)	Contact resistance	≤ 5 mΩ
Rated voltage	63 V	Insulating bodies	PBT
Rated impulse voltage	1.5kV	Contact material	copper alloy
Pollution degree	3	Contact surface	gold plated
Flammability acc. to UL 94 V0 (UL94)		Mechanical working life	>500
Overvoltage categorie	III	Degree of protection	IP67
		Temperature range	-40°C ...+130°C

Male, Crimp terminal

order crimp contacts separately




Contacts	Cable outlet	Designation	Order No.
17	6-9.5mm	M17-MC017-CCT-D9.5-SH	165 017 710 2502
	9-12mm	M17-MC017-CCT-D12-SH	165 017 710 2503

Female, Crimp terminal

order crimp contacts separately



Contacts	Cable outlet	Designation	Order No.
17	6-9.5mm	M17-FC017-CCT-D9.5-SH	165 017 420 2502
	9-12mm	M17-FC017-CCT-D12-SH	165 017 420 2503




Crimp contacts

Crimp contacts 3.6A

3.6A



NO.	Wire gauge(mm ²)	Male	Order No.
①	0.14-0.5	M17-MC3.6G-0.5	101 039 210 0401
NO.	Wire gauge(mm ²)	Female	Order No.
①	0.14-0.5	M17-FC3.6G-0.5	101 039 220 0401



Tools

Crimping tool



Wire gauge	Designation	Order No.
0.09-0.82 mm ²	TL03	198 001 001 0002

Notes: The tools for crimp terminal may influence the product quality and stability. Please select the tools recognized by our company.