

MR23 Circular connector

160V- 10A

Technical characteristics

Specifications			
Specifications	DIN EN 60 664		
	DIN EN 61 984		
Approvals			
Electrical data		Mechanical data	
Number of contacts	9 (8+1)	Housing material	copper alloy,zinc alloy
Rated current	10A	Housing surface	Nickel-plated
mm²/ AWG	0.03-1.0+0.35-2.5	Contact resistance	≤ 5 mΩ
Rated voltage	160 V	Insulating bodies	PBT
Rated impulse voltage	2.5 kV	Contact material	copper alloy
Pollution degree	3	Contact surface	gold plated
Flammability acc. to UL 94	V0 (UL94)	Mechanical working life	>500
Overvoltage categorie	III	Degree of protection	IP67
		Limiting temperature	-40°C ...+130°C

Forward coding, Crimp terminal
order crimp contacts separately




Contacts	Designation	Order No.
9	MR23-009-BK26-OD2.7	181 009 300 1500
	MR23-009-BK26-OD3.2	181 009 300 1501
	MR23-009-BK28-OD3.2	181 009 300 1508

Reverse coding, Crimp terminal
order crimp contacts separately



Contacts	Designation	Order No.
9	MR23-009R-BK26-OD2.7	181 009 300 1504
	MR23-009R-BK26-OD3.2	181 009 300 1505
	MR23-009R-BK28-OD3.2	181 009 300 1510



9pin orward coding 9pin Reverse coding

Designation	A	B	C	D
MR23-009-BK26-OD2.7				
MR23-009R-BK26-OD2.7	26	19.8	Φ2.7/M2.5	3.6
MR23-009-BK26-SE-OD3.2				
MR23-009R-BK26-OD3.2				
MR23-009-BK28-OD3.2	28	22.6	Φ3.2/M3.0	3.7
MR23-009R-BK28-OD3.2				

Crimp contacts

Crimp contacts 9A

9A



NO.	Wire gauge(mm ²)	Male	Order No.
①	0.03-0.34	M23-MC9G-0.34	101 031 210 2501
②	0.14-1.0	M23-MC9G-1.0	101 031 210 0801

NO.	Wire gauge(mm ²)	Female	Order No.
①	0.03-0.34	M23-FC9G-0.34	101 031 220 2501
②	0.14-1.0	M23-FC9G-1.0	101 031 220 0801

NO.	Φa	Φb	Stripping length
①	1.7	0.9	4mm
②	2.1	1.45	4mm


Crimp contacts 20A

20A



NO.	Wire gauge(mm ²)	Male	Order No.
①	0.35-2.5	MR23-MC20G-2.5	101 020 210 1001

NO.	Wire gauge(mm ²)	Female	Order No.
①	0.35-2.5	MR23-FC20G-2.5	101 020 220 1001



Tools

Crimping tool



Wire gauge	Designation	Order No.
0.14-4 mm ²	TL28-2	198 001 001 0039

Notes: The tools for crimp terminal may influence the product quality and stability. Please select the tools recognized by our company.